



HYDRAULIC COUPLERS

Jaw type coupler have special material hardened jaws for extended service life. Body is zinc or Chrome plated. For all hand operated grease gun only (not for power lubricating) Available in 3 or 4 jaws. With non return ball check valve

STANDARD COUPLERS



- ...▶ Heavy constructed steel round body
- ...▶ Available in both 3 or 4 jaws
- ...▶ working pressure recommended 3000 psi

CAT NO.	JAWS	THREAD
30-111	3 Jaws	1/8"BSPT
*30112	3	M10x1
*30113	3	1/8"NPT
30-114	4 Jaws	1/8"BSPT
*30-115	4	M10x1
*30-116	4	1/8"NPT

PROFESSIONAL COUPLERS



- ...▶ Heavy constructed steel body.
- ...▶ High pressure without any deformation hexagonal base for proper installation and removal.
- ...▶ Available in both 3 or 4 jaws
- ...▶ working pressure recommended 6000 psi

CAT NO.	JAWS	THREAD
*30-121	3 Jaws	1/8"BSPT
*30122	3	M10x1
30123	3	1/8"NPT
*30-124	4 Jaws	1/8"BSPT
*30-125	4	M10x1
*30-126	4	1/8"NPT

* Not Shown

HEAVY DUTY COUPLER



- ...▶ Heavy constructed double wall thickness steel body.
- ...▶ hexagonal base for proper installation & remove.
- ...▶ Available in 3 or 4 jaws.
- ...▶ working pressure recommended 10.000 psi.

CAT NO.	JAWS	THREAD
*30-131	3 Jaws	1/8"BSPT
*30-132	3 Jaws	M 10x1
30-133	3 Jaws	1/8"NPT
*30-134	4 Jaws	1/8"BSPT
*30-135	4 Jaws	M 10x1
*30-136	4 Jaws	1/8"NPT

*** Not Shown**