



FLEXIBLE HOSE



- ...▶ Heavy flexible Plastic or rubber construction for hand operated grease gun only.
- ...▶ Zinc plated steel connection with positive crimping excellent for confined area.
- ...▶ Select lengths available in the following variations.
- ...▶ Spring guard added safety and convenience in fitment.
- ...▶ Working pressure 4000 psi.

Plastic hose

CAT NO	CAT NO	CAT NO	DESCRIPTION
1/8"BSPT	m10x1	1/8"NPT	
35-201	*35-221	*35-241	12" length
*35-202	*35-222	*35-242	12"length 1 per card.
*35-203	*35-223	*35-243	12"with standard coupler
35-204	*35-224	*35-244	12"with spring guard

35-205	*35-225	*35-245	12"with spring guard & standard coupler
*35-206	*35-226	*35-246	18"length
*35-207	*35-227	*35-247	18"length 1 per card
35-208	*35-228	*35-248	18"with standard coupler
*35-209	*35-229	*35-249	18"with spring guard
*35-210	*35-230	*35-250	36"length
*35-211	*35-231	*35-251	36"with standard coupler

Rubber hose

CAT NO 1/8"BSPT	CAT NO m10x1	CAT NO 1/8"NPT	DESCRIPTION
35-261	*35-271	*35-281	12" length
*35-262	*35-272	*35-282	12"length 1 per card.
*35-263	*35-273	*35-283	12"with spring guard
35-264	*35-274	*35-284	18"length
35-265	*35-275	*35-285	18"length 1 per card
*35-266	*35-276	*35-286	18"with spring guard

Note:-

- All the couplers are replace with product serial no. 30
- Other length can be made on order.

* Not Shown



This is designed lubricate agricultural Equipment, Equipment, earth moving machinery, motor vehicle etc. Heavy constructed steel body, Zinc Finish With or without check valve (wcv).

THREAD CAN BE CHANGED ACCORDING TO ORDER.



THREAD SIZE	STRAIGHT	STRAIGHT LONG	STRAIGHT FEMALE	30 Deg.	45 Deg.	65 Deg.	90 Deg.	BUTTON HEAD	FUNNEL HEAD
1/4" x 28	*35-601	*35-621			35-661		*35-691		
1/8"NPT	35-602	*35-622	*35-642	*35-652	35-662	*35-682	*35-692	*35-702	*35-712
1/4"NPT	*35-603					*35-683		*35-703	*35-713
3/8"NPT								*35-704	*35-714
3/16"DRIVE	35-605 35-606 (wcv)				*35-665	*35-685			
1/4"DRIVE	35-607 35-608 (wcv)					*35-686			
5/16"DRIVE	35-609 35-610 (wcv)								
6mm	*35-611				*35-671		*35-697		
8mm	*35-612				*35-672		*35-698		
10mm	*35-613				35-673		*35-699		

*** Not Shown**