



SUCTION PUMP

Heavy constructed steel barrel 1.22mm wall thickness pump has single action. That is easy and comfortable working with each stroke fluid is drawn in & it can be used in home, industry, farm & automotive. Need no priming with 12" flexible vinyl hose.

Recommended for oil based fluid, heating oils, motor oil, low & heavy viscosity oil, low & heavy viscosity oil.

Avoid to use with water based fluids, antifreeze. Solvents & acids.



40-701

Chrome plated steel based + plastic cap+ half v pulling rod.



40-702

All painted mat black steel body + plane cap+ back cap with lock with half v type pulling rod.



40-703

All painted mat black steel body + plane cap + back cap with lock with steel T or half v type pulling rod.



40-704

All painted steel steel barrel with wide knurling for grip + chrome plated steel cap+ back cap with plastic T type pulling rod



40-705

All chrome plated steel body + chrome plated cap on both side + with v type pulling rod

TRANSFER PUMP

Heavy constructed steel barrel 1.22mm wall thickness pump has dual action. With every stroke we can sucks and feeds. This design is safe and comfortable to use pump allows for transferring fluid from one container to another in a single stroke with double check valve. With 1 meter vinyl hose for each port.

- ***Recommended for oil based fluid, heating oils, motor oil, low & heavy viscosity oil.**
- ***Avoid to use with water based fluid, antifreeze, solvents & acids.**



40-715 :-

All painted steel body with plastic T - type pulling rod.